



Automatic rewinder for converting PE and PVC film; cling & stretch from 7,5  $\mu\text{m}$  up to 35  $\mu\text{m}$ . Solid construction assure continuous work with top speed 1400 m/min. Together with construction multi V-belt minimize vibrations too minimum. Equipped with multi sensors, simple control panel makes daily operations on machine very friendly. Rewinder works continuously even with thin cores.

Perfectly works both with hand rolls and machine rolls (up to 18 kg), at the same time and in automatic mode. Dedicated system for thin paper cores.

Ergonomic and very friendly for the operator construction gives you more opportunities in rewinding, as slitting system for mini rolls, making double edge in thickness of stretch film or rewinding machine rolls up to 240 mm outer diameter. Rewinder gives you opportunity to rewind cast and blown stretch film. Core takers are compatible to work with various quality and thickness of paper cores.

### ■ KEY BENEFITS:

- speed control;
- acceleration and breaking time control;
- tear off the film by detection;
- end of jumbo roll detection;
- film on the shaft detection;
- online support;
- automatic lubrication system for bearings;
- electrical movement of jumbo roll (left/right);
- slitting for mini rolls - optional;
- double-edge folding - optional.



## ■ PARAMETERS

Types of converted materials	PE stretch & cling, PVC stretch & cling
Dimensions length/width/height	ca. (2000/1900/1800 mm)
Machine weight	ca. 1600 kg
Rated voltage	400V AC/50Hz + N + PE
Rated power	ca. 9,5 kW
Internal core diameter	50 mm, 76 mm
Drive	1 servo drive
Acceleration time	2,7s - 2,9s *depends on jumbo size
Breaking time	2,7s - 2,9s*depends on jumbo size
Internal "master core"	76 mm
Linear speed	0 – 1400 m/min.
Film width	500 mm
Max. diameter of converted roll	up to 240 mm
Max. weight of the master roll	up to 70 kg
Rewinding machine rolls	in auto mode, up to 18 kg
Tension control	mechanical
Working pressure	6 BAR
Compressed air consumption	130 l/min
Exemplary capacity	up to 150-160 tons monthly/2 shifts for 7 hours each



Contact us:



KRAM FC  
ul. Słoneczna 3C  
82-440 Dzierzgoń



tel. +48 55 625 53 23  
e-mail: [export@kramfc.com](mailto:export@kramfc.com)  
[www.kramfc.com/en](http://www.kramfc.com/en)